

Product Specification:



Highlights:

A2B

Ceiling Hoist

- One of the smallest ceiling track hoists
- Dynamo gravity powered charging system automatically charges when in use
- Auto emergency stop and lowering system
- Can be fitted to a curved, straight or H frame



The Astor-Bannerman A2B overhead ceiling track hoist is one of the smallest professional-use hoists on the market. Helping to reduce carer back strain, this ceiling hoist makes patient transfer easier from wheelchair to bath and changing area, or even room to room, whilst preserving the dignity of the user.

A unique dynamo gravity powered charging system within the Astor-Bannerman A2B ceiling hoist means the unit is automatically charged when in use and can remain charged for more than 150 lifts. The A2B ceiling hoist also has an in built emergency lowering system.

The A2B Ceiling hoist can be fitted to a curved, straight or H frame (XY) ceiling track for full room coverage, and the compact design and flexible fitting options mean this hoist can also be installed to the wall or on a free standing gantry. This makes it the ideal patent handling solution for use with assisted baths and showering/changing equipment within domestic and care home bathrooms, bedrooms, wet rooms and Changing Places toilet facilities.

It is operated at the touch of a button to raise and lower the client. The motor can then either transport the client manually (2 function) or via the handset (4 function).

As with all Astor-Bannerman moving and handling equipment, the A2B Ceiling hoist is available with a wide range of options, accessories and slings, and each hoist is made to measure meaning your equipment will be tailored to suit your individual needs.



STANDARD FEATURES

- SWL 200kg/31¹/₂st
- Tape lifting range: 100mm 2500mm (2400mm)
- Cassette Dimensions: 303mm x 240mm x 190mm
- Handset operation
- Gravity powered charging
- Auto emergency stop and lowering
- Quick fit rail system
- 2 Point, 6 hook spreader bar for loop slings
- No lights at night
- Enhanced lifting tape longevity
- 3 Year warranty (Terms and conditions apply)



- Safe Working Load: 250kg/39¼st available
- 2 or 4 Function (powered up/down + left/right)
- Portable & removable hoists available
- Straight, curved or XY track
- Turntables and gates
- Weight scale
- Infra-red hand control
- X-frame 4 point spreader bar
- Manual or powered cradle
- Full range of loop slings
- LOLER testing
- Range of service & maintenance packages including LOLER testing. Please ask for further details.